

FABRIC N SEAT**C025****1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**

Product Code C025

Manufacturer : Selden Research Limited
 Staden Lane Business Park, ,
 Buxton, Derbyshire. SK17 9RZ
 United Kingdom

Product Name FABRIC N SEAT

Tel : 01298 26226
 Fax : 01298 26540
 Email : sales@selden.co.uk

2 HAZARDS IDENTIFICATION

R36/38 Irritating to eyes and skin.

Classification Xi;R36/38.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EINICS No.	CAS No.	Content	Classification
1-METHOXY-2-PROPANOL	203-539-1	107-98-2	1 - 5%	R10
3-BUTOXYPROPAN-2-OL	225-878-4	5131-66-8	1 - 5%	Xi;R36/38
ALCOHOL ETHOXYLATE			1 - 5%	Xi;R38,R41.
SODIUM HYDROXIDE	215-185-5	1310-73-2	1 - 5%	C;R35
Trisodium nitrilotriacetate	225-768-6	5064-31-3	1 - 5%	Xn;R22. Xi;R36.

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

INHALATION	Move the exposed person to fresh air at once., Rinse nose and mouth with water., Get medical attention if any discomfort continues.
INGESTION	Remove victim immediately from source of exposure., DO NOT INDUCE VOMITING!, Rinse mouth thoroughly., Drink plenty of water., Get medical attention.
SKIN CONTACT	Remove affected person from source of contamination., Remove contaminated clothing., Rinse the skin immediately with lots of water., Continue to rinse for at least 15 minutes., Get medical attention if irritation persists after washing.
EYE CONTACT	Promptly wash eyes with plenty of water while lifting the eye lids., Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA	This product is not flammable., Use fire-extinguishing media appropriate for surrounding materials.
SPECIAL FIRE FIGHTING PROCEDURES	Use water to keep fire exposed containers cool and disperse vapours.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS	Wear necessary protective equipment., Absorb in vermiculite, dry sand or earth and place into containers., Flush with plenty of water to clean spillage area.
ENVIRONMENTAL PRECAUTIONS	Any spillage needs to be contained and not allowed to enter water courses

7 HANDLING AND STORAGE

USAGE PRECAUTIONS	Avoid spilling, skin and eye contact.
USAGE DESCRIPTION	Store in tightly closed original container in a dry, cool and well-ventilated place., Keep in original container.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs	STEL - 15 min	Notes
1-METHOXY-2-PROPANOL		100 ppm(Sk)	150 ppm(Sk)	560 mg/m3(Sk)
SODIUM HYDROXIDE	WEL			2 mg/m3

PROTECTIVE EQUIPMENT

ENGINEERING MEASURES	Provide adequate general and local exhaust ventilation.
HAND PROTECTION	Use protective gloves made of:, Rubber (natural, latex).
EYE PROTECTION	Use eye protection.
OTHER PROTECTION	General workwear only

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Clear, Liquid
COLOUR	Blue
BOILING POINT (°C)	> 100 C
RELATIVE DENSITY	1.040 - 1.050 @ 20 °c
pH-VALUE, CONC. SOLUTION	13.5

SOLUBILITY Soluble in water

10 STABILITY AND REACTIVITY

STABILITY Stable under normal temperature conditions., Avoid., Mixing with any other material.
HAZARDOUS DECOMPOSITION PRODUCTS Fire or high temperatures create., Toxic gases/vapours/fumes of., Carbon dioxide (CO₂)., Carbon monoxide (CO).

11 TOXICOLOGICAL INFORMATION

INHALATION May cause irritation to the respiratory system.
INGESTION Liquid irritates mucous membranes and may cause abdominal pain if swallowed., May cause stomach pain or vomiting.
SKIN CONTACT Irritating to skin., Prolonged or repeated exposure may cause severe irritation.
EYE CONTACT Irritation of eyes and mucous membranes.

12 ECOLOGICAL INFORMATION

ECOTOXICITY Not classed as Hazardous to the Environment but release to the environment should be avoided.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION

TRANSPORT LABELS



UN NO. ROAD 1760
UK ROAD CLASS 8
UK ROAD PACK GR. III
ADR CLASS NO. 8
ADR CLASS Class 8: Corrosive substances.
PROPER SHIPPING NAME CORROSIVE LIQUID, NOS (Sodium hydroxide, Trisodium nitrilotriacetate)
UN NO. SEA 1760
IMDG CLASS 8
UN NO. AIR 1760
AIR CLASS 8

15 REGULATORY INFORMATION

LABELLING



Irritant (Xi)

RISK PHRASES R36/38 Irritating to eyes and skin.
SAFETY PHRASES S2 Keep out of the reach of children, S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice., S37/39 Wear suitable gloves and eye/face protection., S46 If swallowed, seek medical advice immediately and show this container or label.
STATUTORY INSTRUMENTS Chemicals (Hazard Information and Packaging) Regulations., Control of Substances Hazardous to Health.
APPROVED CODE OF PRACTICE Classification and Labelling of Substances and Preparations Dangerous for Supply.
GUIDANCE NOTES Workplace Exposure Limits EH40., CHIP for everyone HSG(108).

16 OTHER INFORMATION

GENERAL INFORMATION The following risk phrases relate to the raw materials in the product and not the product itself-
REVISION DATE 20/01/2006
REV. NO./REPL. SDS GENERATED 7
RISK PHRASES IN FULL R36/38 Irritating to eyes and skin.| R10 Flammable.| R35 Causes severe burns.| R38 Irritating to skin., R41 Risk of serious damage to eyes.| R22 Harmful if swallowed., R36 Irritating to eyes.|